

VRE-5513 / VRE-5521

DESCRIPTION

The VRE-5513 and VRE-5521 are Bisphenol-A based epoxy vinyl ester resin, unpromoted and non-thixotropic.

FEATURES AND BENEFITS

- Good wet out/roll out properties
- Low viscosity.
- Provide good chemical resistance.
- Good Mechanical properties.

APPLICATIONS

- Pultrusion, filament winding, compression molding, RTM, and Hand-lay Up process.

TYPICAL LIQUID PROPERTIES

Property	Units	VRE-5513	VRE-5521	Test Method
Acid number (Solution)	Mg KOH/g sample	6 max.		TARQ – 100
Non-volatile content	%	56-61		CCP-300.8
Brookfield viscosity ³	cps		250-450	TARQ - 300
Gel time	Min.	18-24 1	15-25 ²	CCP-503.7
Cure time	Min.	26-46	1-3	CCP-503.7
Exothermic Peak	ФC	149 min.	150-185	CCP-503.7
Stability at 120°C	Hours	1 min.		TARQ - 660
Appearance		Clear		Visual

 $^{^1}$ 0.15% Co (12%), 0.05% DMA, 1.5% Luperox DDM-9 catalyst @25°C; 2 0.15% Co (6%), 0.05% DMA, 1% Luperox DDM-9 catalyst @25°C; 3 LVDV-E, spindle #3, 60 rpm @25°C.

NOTE: Tests results compared with the reported in certificate can be affected due to: batch age, temperature, moisture, type and amount of catalyst, testing equipment and method.



PYSICAL PROPERTIES

Physical properties are shown for fiberglass laminate: These are typical values and are provided for reference only.

Property	Units	VRE-5513	VRE-5521	Test Method
Tensile Strength	Мра	78		ASTM D-638
Tensile Modulus	Мра	3655		ASTM D-638
Elongation	%	7.4		ASTM D-638
Flexural Strength	Мра	146		ASTM D-790
Flexural Modulus	Мра	3350		ASTM D-790
HDT @ 1.82 MPa	°C	101		ASTM D-648
Barcol Hardness		37		ASTM-D-2583

- 1.- Laminate construction: 30% fiberglass to resin ratio.
- 2.- Laminate cured overnight at room temperature and post-cured at 65°C for 5 hours.
- 3.- HDT is evaluated at neat resin casting.

RECOMMENDATIONS

- 1.- The catalyst level should not exceed 2.8% or fall below 1% for proper cure.
- 2.- These products should not be used when temperature conditions are below 16°C, as curing and handling may be adversely affected.
- 3.- Do not add any material different to the catalyst recommended for these products.
- 4.- Do not mix organic peroxides with metallic soaps, amines or any type of accelerators or promoters, because it can result on violent decomposition with fire or explosion.
- 5.- Any additional questions, please contact your Reacciones Químicas SA de CV sales representative.

STORAGE

Uncatalyzed VRE-5513 and VRE-5521 resins, have a usage life of three months from invoice date, when stored at 25°C or below, in a closed, factory sealed opaque containers, and out of direct sunlight, heat sources or moisture. For every 7°C increase in storage temperature, the shelf life is reduced by one half.

SAFETY AND HANDLING

Detailed information for safe handling of VRE-5513 and VRE-5521 resins, can be found on its SDS. For more information, please contact your Reacciones Químicas SA de CV sales representative.



Last Revision: 29/11/2021

DISCLAIMER AND LIMITATION OF LIABILITY

To the best of our knowledge, the information contained herein is accurate. The products sold hereunder shall meet Seller's applicable specifications at time of shipment. Seller's specifications may be subject to change at any time without notice to Buyer. Buyer must give Seller notice in writing of any alleged defect covered by warranty (together with all identifying details, including the product code(s), description and date of purchase) within thirty (30) days of the date of shipment of the product or prior to the expiration of the shipment's quality life, whichever comes first. THE WARRANTY DESCRIBED HEREIN SHALL BE IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. THERE ARE NO WARRANTIES THAT EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. The Buyer's sole and exclusive remedy against Seller shall be for the replacement of the product or refund of the purchase price in the event that a defective condition of the product should be found to exist by the Seller. NO OTHER REMEDY (INCLUDING, BUT NOT LIMITED TO, INCIDENTAL OR CONSEQUENTIAL DAMAGED FOR LOST PROFITS, LOST SALES, INJURY TO PERSON OR PROPERTY, OR ANY OTHER INCIDENTAL OR CONSEQUENTIAL LOSS) SHALL BE AVAILABLE TO THE BUYER. The sole purpose of this exclusive remedy shall be provided Buyer with replacement of the product or refund of the purchase price of the product if any defect in material or workmanship is found to exist. This exclusive remedy shall not be deemed to have failed its essential purpose so long as Seller is willing and able to replace the defective products or refund the purchase price. Final determination of the suitability of the material for use contemplated, the manner of use and suggested use infringed any patents is the sole responsibility of the Buyer.